



F&F Filipowski sp. j.
Konstantynowska 79/81 95-200 Pabianice
phone/fax: (+48 42) 215 23 83 / 227 09 71 POLAND
http://www.fif.com.pl e-mail: biuro@fif.com.pl

INPUT SIGNAL SEPARATOR

SEP-02

WARRANTY. The F&F products are covered by a warranty of the 24 months from the date of purchase. Effective only with proof of purchase. Contact your dealer or directly with us. More information how to make a complaint can be found on the website:
www.fif.com.pl/reklamacje



Do not dispose of this device in the trash along with other waste! According to the Law on Waste, electro coming from households free of charge and can give any amount up to that end point of collection, as well as to store the occasion of the purchase of new equipment (in accordance with the principle of old-for-new, regardless of brand). Electro thrown in the trash or abandoned in nature, pose a threat to the environment and human health.

Purpose

SEP-02 is used for the separation of control signals in automation systems with dedicated subgroups of control and central control.

Functioning

The control signal is passed in the direction of 1 → 2; 3 → 4.
In the opposite direction the signal is blocked.

Technical data

load current	<1A 1000V
working temperature	-25÷50°C
terminal	2.5mm ² screw terminals
dimensions	Ø55, h=13mm
mounting	on flat base or in flush-mounted Ø60

Wiring diagram

See the forefront of the device

D170425

- 5 -

- 6 -

- 7 -

D140930

- 8 -